




The First Choice Of Knowledgeable FARMERS!



3 MB HYDRAULIC REVERSIBLE PLOUGH

**SUPER** HYDRAULIC REVERSIBLE PLOUGH



## Shear Bolt Safety Protection:



Pushpak Super Plough is equipped with shear bolt device to avoid additional load such as stones, tree roots or rock ridges. Replacement of new shear bolt can be done easily and quickly without suffering the work..

## Center Adjustment Setting




Center adjustment setting makes it easy to adjust front furrow width and tractor pull line independently of each other.

## Working Width Adjustment




Different type of soil and moisture content, all have different demands for working width. For this easy and quick adjustment is given. It can be adjusted for 10", 12" and 14".

## Underbody and Interbody clearance



Large Underbody and Interbody clearance avoids the blockages even at close settings for furrows.

## Reliable Turnover and Infinite Angle Adjustment









Pushpak Super Plough is equipped with hydraulic turnover device which gives precise, safe and quick turnover action. Also independent LH and RH work angle can be adjusted.

## Mould Board



Super mould board is manufactured on unique dies to give smooth soil turnover, increase in fuel efficiency etc.

## Technical Specification

Model	Under Body Clearance	Working Width	Working Depth	Distance Between two Working Point	Weight	Description	Power	
								
	cm	cm	cm	cm	Kg (Approx)		HP	Kw
<b>SHP2-55</b>	70	50 - 70	30 - 40	83	455	Two Furrow	55 - 65	40 - 48
<b>SHP3-75</b>	70	75 - 105	30 - 40	83	585	Three Furrow	70 - 90	55 - 66

Note : Technical Specifications are subject to change without prior notice

Authorised Distributor :



Manufactured by :

**Deccan Farm Equipment Pvt. Ltd.**

C - 35, M. I. D. C., Shirol, Kolhapur 416 122, M.S. (INDIA), Phone : +91 230 2468904  
 Email : sales@deccanequipments.com Web : <http://www.deccanequipments.com>





The First Choice Of Knowledgeable FARMERS!



**DELUX** HYDRAULIC  
REVERSIBLE PLOUGH



**DELUX** MECHANICAL  
REVERSIBLE PLOUGH

The First Choice Of Knowledgeable FARMERS!



Heavy Duty Head Stock







Mould Board



Regular Head Stock

### Technical Specifications \*

#### **DELUX** Hydraulic Reversible Plough

Model	Working Width	Working Depth	Weight	Power	
					
	cm	cm	Kg (Approx)	HP	Kw
<b>DHP 2 - 45</b>	30	30	385	45 - 50	33 - 37
<b>DHP 2 - 35</b>	27	30	365	35 - 40	26 - 29
<b>DHP 2 - 25</b>	22	22	238	25 - 30	18 - 22

#### **DELUX** Mechanical Reversible Plough

<b>DMP 2 - 45</b>	30	30	385	45 - 50	33 - 37
<b>DMP 2 - 35</b>	27	30	365	35 - 40	26 - 29
<b>DMP 2 - 25</b>	22	22	238	25 - 30	18 - 22

\* Technical Specifications are subject to change without prior notice

Authorised Distributor :



Manufactured by :

**Deccan Farm Equipment Pvt. Ltd.**


C - 35, M. I. D. C., Shirol, Kolhapur 416 122, M.S. (INDIA), Phone : +91 230 2468904  
Email : sales@deccanequipments.com Web : <http://www.deccanequipments.com>





The First Choice Of  
Knowledgeable FARMERS !


# Pushpak Ratoon Manager



**PUSHPAK**  
AGRI EQUIPMENTS

*Deccan* FARM EQUIPMENT  
PRIVATE LIMITED  
KOLHAPUR






Cutting Blade Assembly



Fertilizer Application Unit (Optional)



Ridges Cutting Disc (Optional)



Before Operation




After Operation

## Special Features and Benifits of " PUSHPAK RATOON MANAGER "

- ⊙ Ratoon manager cuts the uneven height of sugarcane stubbles at ground level.
- ⊙ For proper germination of ratoon crop su garcane stubbles needs to shaveat ground level.
- ⊙ Ratoon crop matures early and maturity will be at same time.
- ⊙ Proper ratoon management will increases the yield of sugarcane.

### Basic Model



### TECHNICAL SPECIFICATIONS

Sr. No.	Description	* Approx. Details
1)	Length	1780 mm
2)	Width	1270 mm
3)	Height	1000 mm
4)	Weight	300 kg
5)	Tractor HP	35 HP & Above
6)	PTO RPM of Tractor	540 rpm
7)	Field Coverage Capacity	0.3 to 0.4 acre/hour
8)	Fuel Consumption	8 to 10 litre/acre

\* Figures Mentioned are Approximately

\* Consumption & timings are subject to ideal conditions.

Authorised Dealer

Manufacturer :

*Deccan* FARM EQUIPMENT  
PRIVATE LIMITED

C-35, M.I.D.C., Shirol, Kolhapur(MH) 416122, India.

Phone : +91-230-2468904

Website: <http://www.deccanequipments.com>


Email: [sales@deccanequipments.com](mailto:sales@deccanequipments.com)





The First Choice Of  
Knowledgeable FARMERS !

# Pushpak Ratoon Manager



*Deccan* FARM EQUIPMENT  
PRIVATE LIMITED  
KOLHAPUR



Cutting Blade Assembly



Fertilizer Application Unit  
(Optional)



Ridges Cutting Disc  
(Optional)



Before Operation



After Operation



## Special Features and Benifits of " PUSHPAK RATOON MANAGER "

- Ratoon manager cuts the uneven height of sugarcane stubbles at ground level.
- For proper germination of ratoon crop sugarcane stubbles needs to shave at ground level.
- Ratoon crop matures early and maturity will be at same time.
- Proper ratoon management will increases the yield of sugarcane.



Basic Model

## TECHNICAL SPECIFICATIONS

Sr. No.	Description	* Approx. Details
1)	Length	1780 mm
2)	Width	1270 mm
3)	Height	1000 mm
4)	Weight	300 kg
5)	Tractor HP	35 HP & Above
6)	PTO RPM of Tractor	540 rpm
7)	Field Coverage Capacity	0.3 to 0.4 acre/hour
8)	Fuel Consumption	8 to 10 litre/acre

\* Figures Mentioned are Approximately  
\* Consumption & timings are subject to ideal conditions.

Authorised Dealer

Manufacturer :

*Deccan* FARM EQUIPMENT  
PRIVATE LIMITED

C-35, M.I.D.C., Shirol, Kolhapur (MH) 416122, India.  
Phone : +91-230-2468904  
Website: <http://www.deccanequipments.com>  
Email: [sales@deccanequipments.com](mailto:sales@deccanequipments.com)





The First Choice Of  
Knowledgeable **FARMERS** !



**PUSHPAK ROOTER**

Deccan Farm Equipment Pvt. Ltd.  
Kolhapur 416 122



Various Models of Rooter  
For Any Tractor !

**REGULAR ROOTER MODEL**



**HEAVY DUTY ROOTER**



Authorised Dealer

**SPECIAL FEATURES :**

- \* Specially usefull for removing sugarcane & other Crop roots.
- \* Removes roots totally & thoroughly.
- \* Deep cultivation of soil.
- \* Compactness of soil does not take place.
- \* Proper ground level maintained.
- \* Next crop can be taken up immediately.
- \* Extremely efficient due to specially designed blades.
- \* No extra load on the tractor. \* Speedy work.
- \* Specially design of PTO joint for
- \* Easy availability of spare parts & safety operating.
- \* Easy to attach tractor no any more persons required.
- \* Zero maintenance.
- \* New heavy design of Three way link.
- \* Both side support to gear box.
- \* Heavy duty gear box design.



Indian P.T.O. Joint



Imported P.T.O. Joint



R.B. = L. Type Blades



R.T. = Tine Type Blades

**TECHNICAL SPECIFICATIONS**

**REGULAR ROOTER MODEL**

Model & P.T.O. R.P.M.	Feet	H.P. of Tractor	Working Width (Approx)	Working Depth (Approx)	No. Of Tines/ Blades	Total Weight (Approx)
R.B. 100 (540)	3'	25 To 35 H.P.	102 cm	6 To 8 Inch	27 NOS	255 kg
R.B. 100 (1000)	3'	25 To 35 H.P.	102 cm	6 To 8 Inch	27 NOS	285 kg
R.B. 125 (540)	4'	35 To 60 H.P.	116 cm	6 To 8 Inch	30 NOS	275 kg
R.B. 125 (1000)	4'	35 To 60 H.P.	116 cm	6 To 8 Inch	30 NOS	300 kg
R.B. 150 (540)	5'	45 To 60 H.P.	150 cm	6 To 8 Inch	36 NOS	325 kg
R.B. 150 (1000)	5'	45 To 60 H.P.	150 cm	6 To 8 Inch	36 NOS	350 kg

**HEAVY DUTY ROOTER 540 RPM**

Model	Feet	H.P. of Tractor	Working Width (Approx)	Working Depth (Approx)	No. Of Tines/ Blades	Total Weight (Approx)
PLB 150	5'	45 To 55 HP	150 cm	6 TO 7 inch	36 NOS	400 kg
PLB 180	6'	55 To 65 HP	180 cm	6 TO 7 inch	42 NOS	465 kg
PLB 210	7'	60 To 75 HP	210 cm	6 TO 7 inch	48 NOS	570 kg
PLB 240	8'	70 To 85 HP	240 cm	6 TO 7 inch	54 NOS	655 kg



**PUSHPAK ROOTER**

MANUFACTURER :

**Deccan Farm Equipment Pvt. Ltd.**

C -35, M.I.D.C., Shirol, Kolhapur 416 122, M.S. (INDIA)  
Tel.: +91 230 2468904, Fax: +91 230 2468905  
Email : sales@deccanequipments.com  
Web : http://www.deccanequipments.com



## Various Models of Rooter For Any Tractor !



**MULTI SPEED GEARBOX**



**SINGLE SPEED GEARBOX**



**GEAR DRIVE**



**CHAIN DRIVE**

## **SPECIAL FEATURES :**

- ✓ Specially useful for pulverizing the soil.
- ✓ Crop roots mixes thoroughly with the soil, which helps in preparing organic manure.
- ✓ Compactness of soil does not take place.
- ✓ Proper ground level maintained.
- ✓ Next crop can be taken up immediately.
- ✓ No extra load on the tractor. ✓ Speedy work.
- ✓ Easy availability of spare parts.
- ✓ Easy attachment to tractor.
- ✓ Both side support to gear box.
- ✓ Heavy duty gear box design.



**P.T.O. Shaft**









**L. Type Blade Model**



**Tine Type Model**

## **TECHNICAL SPECIFICATIONS**

								
Model	No. of Blades	Working Width*		Working Depth*		Approx Weight*	Tractor	
	n	cm	inch	cm	inch	Kg	HP	kw
RBM125G	30	122	48	15-20	6-8	290	40-50	29-37
RBM155G	36	153	60	15-20	6-8	320	45-60	33-45
RBM185G	42	183	72	15-20	6-8	420	55-70	40-52
RBM205G	48	214	84	15-20	6-8	480	70-90	52-67

Note \* Specifications are subject to change without prior notice.

\* Weight & Sizes are near approximation.

## **MANUFACTURER :**

**Deccan Farm Equipment Pvt. Ltd.**

C -35, M.I.D.C., Shirol, Kolhapur 416 122, M.S. (INDIA)

Tel.: +91 230 2468904

Email : sales@deccanequipments.com

Web : <http://www.deccanequipments.com>

**Authorised Dealer**